OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER 16 RANGE \_\_\_\_5\_ 8500 PARTY CHIEF: Wilcoxen CREW: TYPE OF MARKER: Harrison in grass median METHOD OF ESTABLISHMENT: County: 6-22-97 Section IN. S.P.C. E ZONE NAD 16051902 508250.5617(m) NAME: N: E: 69801.7311(m) ليا Alsace Place 8450 2. 48 3. 90.16 38th St. 3800 N 165.7'+/-6. 90.56 5.

38th St. 3800 N

Original post set 1820 by Hendricks with witness: 10" elm N 35 W 17 links; 8" dogwood S 22 E 21 links per Marion County Atlas pg. 15. Hosbrook 1-28-1874 called rock with witness: 18" ash N 36 1/2 E 40 links per Warren Township Legal Survey Book pg. 9. MCSO called for wooden hub. McLand 7-8-71 called an iron pin. Fortner 3-17-75 called iron pin 5" down. Cleveland 12-29-82 called PK nail. Gries 8-2-88 called same. Wilcoxen excavated 8-20-93 set Harrison. No monument was found. Re-tied 6-22-97.

51902	
DISTANCE	DESCRIPTION
60.48	Due N to 4"x4" subdivision monument
67.29	PK nail SE PwP#58-421 A 12"up
90.16	Cut 'x' SW curb inlet
90.56	Cut 'x' NW curb inlet
61.19'	Mag nail w/brass washer W PwP#43-421B 24"up
2.45	Due W to brass plug in concrete
165.7'	Due W to approximate C/L of Alsace Place 8450 F
	67.29' 90.16' 90.56' 61.19' 2.45'